




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61F 5/01		A1	(11) International Publication Number: WO 99/18896
			(43) International Publication Date: 22 April 1999 (22.04.99)
(21) International Application Number: PCT/GB98/03068			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 12 October 1998 (12.10.98)			
(30) Priority Data:			
9721863.0 15 October 1997 (15.10.97) GB			
9814726.7 7 July 1998 (07.07.98) GB			
(71)(72) Applicant and Inventor: WATTS, Robert, John [GB/GB]; Venards Cottage, North Gorley, Fordingbridge, Hampshire SP6 2PJ (GB).			Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(74) Agents: PURVIS, William, Michael, Cameron et al.; D. Young & Co., 21 New Fetter Lane, London EC4A 1DA (GB).			

(54) Title: ANKLE-FOOT ORTHOSIS



(57) Abstract

One embodiment provides an ankle-foot orthosis (32) for resisting plantarflexion of a patient's foot, the orthosis (32) comprising: a resiliently flexible sock-like structure (34) enveloping, in use, at least a portion of a patient's lower leg in the vicinity of the ankle and at least a portion of the plantar (46) and dorsal (48) aspects of the patient's foot. Another embodiment provides an ankle-foot orthosis (1) for resisting plantarflexion of a patient's foot, the orthosis (1) comprising: a resilient rib (3) locatable, in use, along and in abutment with at least a portion of the dorsal aspect of the patient's foot and at least a portion of the patient's lower leg, the orthosis (1) comprising means (7) for securing the rib (3) to the patient's foot and lower leg.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

ANKLE-FOOT ORTHOSIS

This invention relates to ankle-foot orthoses.

Orthoses are mechanical devices which impose forces upon a limb of a patient and can be used for a variety of different purposes. For example, orthoses may be provided for supportive, functional, corrective or protective purposes, or for a combination of these. Ankle-foot orthoses are typically provided to provide protection to the ankle and foot of a patient as well as to provide support against excessive plantarflexion or dropping of the foot. In addition to this resistive function, they may also be employed to assist dorsiflexion of the patient's foot during the push off phase of the patient's gait.

Foot plantarflexion is a medical condition that can arise from a variety of causes, for example disease or congenital abnormality. Patients affected by this condition typically experience difficulty in walking as they must lift their foot excessively from the ground in order to avoid stumbling.

A variety of different ankle-foot orthoses have previously been proposed for resisting plantarflexion, and in some cases for additionally assisting dorsiflexion. Figures 1a, 1b, 2a and 2b illustrate two of these previously proposed devices.

Figure 1a illustrates one previously proposed ankle-foot orthosis before it is assembled on a patient. The orthosis 10 must be used in conjunction with a shoe 12 that provides close contact between the shoe and the foot in the region of the instep. The orthosis 10 comprises a pair of supporting metal uprights 14, one connected to either side of the shoe 12 in the region of the heel 16. The connections each comprise a plantarflexion stop 18 that resists foot drop and may also include springs (not shown) to assist dorsiflexion. The upper ends of the uprights are connected to a supporting strap 20 which is securable about the patient's calf. With reference to Figure 1b, it can be seen that the supporting strap 20 provides support about the patient's calf, and that the plantarflexion stops 18 and shoe 12 provide support under the foot of the patient to resist plantarflexion.

Figures 2a and 2b illustrate another previously proposed orthosis device which must also be used in conjunction with a shoe that provides close contact between the shoe and the foot in the region of the instep. In this example, the orthosis 22

comprises a one-piece plastics moulding 24 which comprises a calf abutting region 26 and a sole abutting region 28. The top of the calf abutting region 26 is provided with a closure mechanism 27 that enables the device to be secured to the calf of a patient. The sole abutting region 28 acts in conjunction with the shoe 30 to support the foot of the patient. The stiffness of the plastics moulding and the shape thereof in the region of the ankle defines the amount of resistance to plantarflexion. If more resistance is required, then the gap across the front of the ankle can be reduced, or the stiffness of the plastics can be increased.

Both of the aforementioned previously proposed devices adequately support the foot of a patient to resist plantarflexion. However, they both exhibit serious deficiencies that make them highly unpopular with patients.

A first disadvantage is that both of the previously proposed orthoses are large bulky devices which are clearly visible when worn. Thus, the patient's illness or abnormality is immediately apparent to others and this can adversely affect the patient's state of mind. This problem can be particularly apparent with child patients as the orthosis is an immediately obvious difference which other children can ridicule. It can also be a serious problem for adult patients as a visible device immediately labels them as a disabled or abnormal person with corresponding ramifications for their personal and working lives.

A further disadvantage is that both of these previously proposed devices must be worn with shoes. Thus, if a patient wished to walk without shoes or to go swimming, for example, then they would have to do so without any means for resisting plantarflexion.

A further disadvantage is that these previously proposed devices can cause extreme discomfort when worn. This problem is particularly apparent with the orthosis of Figures 2a and 2b as the device extends under the foot of the patient and thus the full weight of the patient bears upon the device when the patient walks.

Yet another disadvantage is that both of these previously proposed devices are difficult and time consuming to put on and take off. Furthermore, the second device often requires the fabrication of special shoes as it is often not possible to fit the device within normal off-the-shelf shoes. Finally, both devices are expensive to make

and fit as they must be closely fitted to the feet and legs of the patient, and as they are made from relatively expensive materials.

It is an object of aspects of the invention to alleviate some or all of these disadvantages.

5 In accordance with the invention, there is provided an ankle-foot orthosis for resisting plantarflexion of a patient's foot, the orthosis comprising: a resiliently flexible sock-like structure enveloping, in use, at least a portion of a patient's lower leg in the vicinity of the ankle and at least a portion of the plantar and dorsal aspects of the patient's foot.

10 Thus, this aspect of the invention provides a discrete arrangement which adequately resists plantarflexion without requiring the patient to wear a shoe.

Preferably the orthosis comprises a reinforcing means for further resisting planterflexion of the foot. The reinforcing means may be a length of tape, the ends of the tape being joined together to form a figure-of-eight passing under the instep,
15 behind the ankle and crossing on the dorsal aspect of the foot. Alternatively, the reinforcing means may comprises a rib running along at least a portion of the dorsal aspect of the foot and substantially midway between the medial malleolus and the lateral malleolus. Preferably the reinforcing means has a greater resilience than the sock-like structure.

20 The sock-like structure may be defined by the rib and a pair of straps, one secured to either end of the rib and respectively securable about the plantar aspect of the foot and the portion of the patient's lower leg in the vicinity of the ankle.

Preferably, the orthosis comprises an insertion slit extending midway between the medial malleolus and the lateral malleolus towards the calcaneum, means being
25 provided to securely close the slit once the patient's foot has been inserted in the orthosis.

The closing means may comprise a mechanical hook and loop fastener, a set of hoops or hooks being provided adjacent one edge of the slit and a corresponding set of hooks or hoops being provided on a closure member affixed to the other side
30 of the slit, respective hooks and loops being connectable to securely close the slit. Alternatively, the closing means may comprise a zip fastener secured to opposite sides

of the slit. As a further alternative, the closing means may comprise a set of eyelets closable by a lace.

Preferably, the orthosis envelops the dorsal and plantar aspects of the foot without enveloping the toes. Preferably, the orthosis envelops the plantar aspect of
5 the foot without enveloping the calcaneum. The orthosis could envelop the calcaneum if, for example, mechanical correction of the heel bone is required. The device may also be contoured on the surface abutting, in use, the plantar aspect of the foot to aid support of the metatarsals and to position the foot correctly.

Preferably, the sock-like structure is of silicone. Preferably, the sock-like
10 structure is a 35 shore silicone elastomer, or a higher or lower shore silicone elastomer. Preferably, the reinforcing means is of silicone.

Preferably, the orthosis is skin coloured and/or fabricated by injection moulding. The orthosis could alternatively be brightly coloured so as to appeal to children.

15 In accordance with a second aspect of the invention, there is provided a kit comprising a plurality of orthoses as described herein, the orthoses being of varying size and shape for fitting to feet of different sizes and shapes. The kit may also comprise differently coloured orthoses to allow the matching of the colour of the orthosis to the skin colour of the patient.

20 In accordance with a further aspect of the invention, there is provided an ankle-foot orthosis for resisting plantarflexion of a patient's foot, the orthosis comprising: a resilient rib locatable, in use, along and in abutment with at least a portion of the dorsal aspect of the patient's foot and at least a portion of the patient's lower leg, the orthosis comprising means for securing the rib to the patient's foot and lower leg.

25 In one embodiment, the securing means comprises a first strap means securable about one end of the rib and the patient's lower leg, and a second strap means securable about the other end of the rib and the patient's foot.

In another embodiment, the securing means comprises a first strap means securable about one end of the rib and the patient's lower leg and a shoe for securing
30 the other end of the rib to the patient's foot.

In another embodiment, the securing means comprises an adhesive, at least end

portions of the rib being adhered to the patient's lower leg and foot.

In any event, it is preferred that the rib is of plastics, such as polypropylene or ortholene.

Preferably, the orthosis is skin coloured and/or fabricated by injection
5 moulding. The orthosis could be formed by stamping from sheet material. The orthosis could be brightly coloured so as to appeal to children.

In accordance with another aspect of the invention, there is provided a kit comprising a plurality of orthoses as described herein, the orthoses being of varying size and shape for fitting to feet of different sizes and shapes. The kit may also
10 comprise differently coloured orthoses to allow the matching of the colour of the orthosis to the skin colour of the patient.

Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figures 1a and 1b are schematic representations of one previously proposed
15 orthosis;

Figures 2a and 2b are schematic representations of another previously proposed orthosis;

Figure 3 is a schematic representation of an orthosis according to a first aspect of the invention; and

20 Figure 4 is a schematic representation of an orthosis according to a second aspect of the invention.

Figure 5 is a schematic representation of an orthosis according to a third aspect of the invention;

Figure 6 is a side view of the orthosis of Figure 5; and

25 Figure 7 is a schematic representation of an orthosis according to a fourth aspect of the invention.

With reference to Figure 3, the orthosis 32 comprises a resiliently flexible sock-like structure 34 and a reinforcing means 36 (shown in ghost), which in this embodiment is a tape 38 - the ends of which are joined together to form a figure-of-
30 eight which passes under the instep, behind the ankle and crosses on the dorsal aspect of the foot. The reinforcing means may be formed integrally with the sock-like

structure or, alternatively, the reinforcing means may be formed separately and subsequently inserted within the sock-like structure.

The resilience of the sock-like structure and the reinforcing means are chosen, and may be varied, in dependence upon the degree to which the patient suffers from plantarflexion. Indeed, the reinforcing means 36 can be dispensed with if sufficient
5 resistance to plantarflexion is provided by the sock-like structure 34. It is preferred for the resilience of the reinforcing means 36, if provided, to be greater than that of the sock-like structure 34.

In this embodiment, the orthosis 32 envelops a portion of the patients lower leg
10 which preferably includes the medial malleolus 40 (the inside of the ankle) and the lateral malleolus 42 (the outside of the ankle), the calcaneum 44 (the heel), a portion of the plantar aspect 46 of the foot (the sole of the foot) and a portion of the dorsal aspect 48 of the foot (the back of the foot). In this embodiment, the toes 49 of the foot are not enveloped by the orthosis, although they could be enveloped if desired.
15 It is preferred that the orthosis extends beyond the medial and lateral malleoli.

The sock-like structure 34 is provided with a slit (not shown) which extends in a direction towards the calcaneum between the medial and lateral malleoli. In this embodiment, the slit is closable by a mechanical hook and loop fastener 50, such as velcro®. One portion of the fastener (ie. either a hook portion or a loop portion) is
20 affixed to one side of the slit. The other portion of the fastener 50 is affixed to a strap 52 that is affixed to the other side of the slit.

Figure 4 shows a second embodiment of the invention wherein the orthosis 32 is provided with a zip fastener 54, respective parts of which are secured to either side of the slit. In this embodiment, the sock-like structure 34 does not envelop the
25 calcaneum 44 of the foot. It has been found that the orthosis 32 can be made significantly more comfortable if both the calcaneum 44 and toes 49 are not enveloped by the sock-like structure 34. In this embodiment, the reinforcing means comprises a rib 56 which extends partway along the dorsal aspect of the foot. The rib may be formed integrally with the orthosis. Alternatively, the rib may be removably insertable
30 into a pocket provided on the dorsal aspect of the foot to allow for the stiffness of the rib, and/or the angle of support (by inserting differently shaped ribs), to be changed

if desired.

The orthosis of either embodiment may be coloured so that it can be matched to the skin colour of the patient, and may be provided in a variety of different sizes and shapes. The orthosis is preferably manufactured by injection moulding.
5 Alternatively, the orthosis may be manufactured by milling (as described below) and subsequently building up layers of the device upon a suitable cast.

The orthosis may be of a variety of different materials chosen to have a suitable resilience. For example, the orthosis could be of rubber, silicone, plastics or of any other material apparent to persons skilled in the art. Preferably the orthosis is
10 of 35 shore silicone elastomer. The orthosis may be of a greater or lesser shore value depending upon the particular needs of the patient to which it is to be fitted. The reinforcing means may be of silicone, with a chosen shore value, or may be of any other material apparent to persons skilled in the art. The reinforcing means could be of the same material as the sock-like structure, or could be of a different material. For
15 example, in the arrangement of Figure 4, the rib may be of a metal.

Two suitable elastomers are sold under the product names HCR9960 and MED4035 by Nusil Technology of 1050 Cindy Lane, Carpinteria, California, USA. HCR9960 has a working time of approximately 12 hours and MED4035 has a shorter working time of approximately 3 to 4 hours, after which the elastomer cures. The
20 elastomers are thermo-setting and are strained through a 200 mesh screen to remove particulate contaminants.

The elastomers are supplied as A and B components which are preferably combined in equal portions on a two roll mill, or other suitable device, prior to use. A suggested sequence for blending the two components is to first soften part B on the
25 mill and then soften part A, after which an equal weight of part B should be added to part A and then thoroughly mixed. At this stage, it is recommended to keep the temperature of the material as low as possible so as to maximise the shelf life of the elastomer. The mixture may then be manually fitted to a plaster cast of a patient's foot, or more preferably supplied to injection moulding apparatus to mould a suitably
30 shaped orthosis. Curing of the blended elastomer may be accelerated by heat and can take from 3 to 4 hours. The cure may be inhibited by any ambient traces of organic

rubbers and other substances and thus it is preferred for the fabrication of the orthosis to be conducted in a thoroughly cleaned area.

Figure 5 is a schematic representation of another embodiment of orthosis 1 that comprises a resilient rib 3 that is locatable in use along the dorsal aspect of the patient's foot 5. As shown, the orthosis 1 extends from approximately the base of the patient's toes up to the lower portion of the patient's shin.

The rib 3 is formed of a material that is preferably relatively light-weight and resilient - such as a plastic. A preferred material is ortholene or polypropylene, but numerous other suitable materials (such as a metal, an alloy or carbon fibre or similar material for example) will be apparent to persons skilled in the art. The orthosis could be injection moulded, or for a more precise fit could be individually fitted to a patient's foot.

In order for the orthosis to benefit the patient, it must somehow be secured to the patient's foot. In the embodiment of Figure 5, the orthosis 1 is secured to the foot 5 by way of a pair of straps 7, which in the preferred embodiment include mechanical hook-and-loop fasteners (not shown) such as velcro^R that enable the straps 7 to be secured around the patient's foot and lower leg respectively. Alternative fastening mechanisms, such as pop fasteners, could be provided in addition or instead of velcro^R. When the straps are secured about the patient's foot and lower leg, the orthosis 1 is secured to the patient's foot and plantarflexion is resisted. The arrangement of Figure 5 is particularly advantageous for use in warmer climates as the majority of the patient's foot is not covered by the orthosis 1.

Figure 6 is a side view of the orthosis 1 of Figure 5 illustrating the points at which pressure is applied to the patient's foot by the device. As shown, the orthosis 1 applies pressure to the patient's foot at three discrete locations (i), (ii) and (iii). Application of pressure to the foot at these three locations causes plantarflexion to be resisted whilst also aiding dorsiflexion. In this way, the orthosis 1 aids the patient during all stages of the walking motion. Furthermore, the orthosis 1 shown is considerably more comfortable for the patient to wear than previously proposed devices as it does not extend beneath the foot and thus the weight of the patient does not bear upon the orthosis 1 during walking.

A further embodiment of the invention is shown in Figure 7. This embodiment of the invention is primarily designed for use in conjunction with a shoe 9, and comprises an orthosis 1 of polypropylene, for example, and a single strap 11 provided at the end of the reinforcing means closest to the patient's leg, in use. Securing the strap 11 around the patient's lower leg and inserting the foot 5 and orthosis 1 within a shoe 9 provides an orthosis that is capable of resisting plantarflexion of the patient's foot. As an alternative to providing a strap, the upper end of the orthosis could be adhered to the patients lower leg.

If the straps of the orthosis of Figure 5 are removably attached to the rib 3, then the orthosis of Figure 5 could be converted for use with a shoe, as shown in Figure 7, simply by removing the lower strap.

As a further alternative that is not illustrated in the drawings, the straps could be dispensed with and the rib could then be adhered at least at the ends thereof to the Patient's lower leg and foot. The adhesive could be any adhesive suitable for bonding articles to skin.

The orthosis of either embodiment may be coloured so that it can be matched to the skin colour of the patient, and may be provided in a variety of different shapes and sizes.

The orthosis may be of a variety of different materials chosen to have a suitable resilience. For example, the orthosis could be of rubber, silicone, plastics, carbon fibre or of any other material apparent to persons skilled in the art. In a preferred example, the orthosis is of 35 shore silicone elastomer. The orthosis may be of a greater or lesser shore value depending upon the particular needs of the patient to which it is to be fitted.

It will be understood, of course, that the invention has been described herein by way of example only and that modifications may be made within the scope of the invention.

CLAIMS

1. An ankle-foot orthosis for resisting plantarflexion of a patient's foot, the orthosis comprising: a resiliently flexible sock-like structure enveloping, in use, at least a portion of a patient's lower leg in the vicinity of the ankle and at least a portion of the plantar and dorsal aspects of the patient's foot.
2. An orthosis according to Claim 1, comprising a reinforcing means for further resisting planterflexion of the foot.
3. An orthosis according to Claim 2, wherein the reinforcing means comprises a length of tape, the ends of the tape being joined together to form a figure-of-eight passing under the instep, behind the ankle and crossing on the dorsal aspect of the foot.
4. An orthosis according to Claim 2, wherein the reinforcing means comprises a rib running along at least a portion of the dorsal aspect of the foot and substantially midway between the medial malleolus and the lateral malleolus.
5. An orthosis according to Claim 4, wherein the sock-like structure is defined by the rib and a pair of straps, one secured to either end of the rib and respectively securable about the plantar aspect of the foot and the portion of the patient's lower leg in the vicinity of the ankle.
6. An orthosis according to any of Claims 2 to 5, wherein the reinforcing means has a greater resilience than the sock-like structure.
7. An orthosis according to any of Claims 1 to 6, comprising an insertion slit extending susbtantially midway between the medial malleolus and the lateral malleolus at the back of the ankle towards the calcaneum, means being provided to securely close the slit once the patient's foot has been inserted in the orthosis.

8. An orthosis according to Claim 7, wherein the closing means comprises a mechanical hook and loop fastener, a set of hoops or hooks being provided adjacent one edge of the slit and a corresponding set of hooks or hoops being provided on a closure member affixed to the other side of the slit, respective hooks and loops being connectable to securely close the slit.

9. An orthosis according to Claim 7, wherein the closure member comprises a zip fastener secured to opposite sides of the slit.

10. An orthosis according to Claim 9, wherein the closure member comprises a set of eyelets provided on either side of the slit, the slit being closable by a lace fed through the eyelets.

11. An orthosis according to any preceding claim, wherein the orthosis envelops at least a portion of the dorsal and plantar aspects of the foot without enveloping the toes.

12. An orthosis according to any preceding claim, wherein the orthosis envelops at least a portion of the plantar aspect of the foot without enveloping the calcaneum.

13. An orthosis according to any preceding claim, wherein the sock-like structure is of silicone.

14. An orthosis according to Claim 13, wherein the sock-like structure is a 35 shore silicone elastomer.

15. An orthosis according to Claim 2 and to any of Claims 3 to 14 when dependent upon claim 2, wherein the reinforcing means is of silicone.

16. An orthosis according to Claim 2 and to any of Claims 3 to 14 when dependent upon claim 2, wherein the reinforcing means is of a different material to that of the

sock-like structure.

17. An ankle-foot orthosis for resisting plantarflexion of a patient's foot, the orthosis comprising: a resilient rib locatable, in use, along and in abutment with at least a portion of the dorsal aspect of the patient's foot and at least a portion of the patient's lower leg, the orthosis comprising means for securing the rib to the patient's foot and lower leg.

18. An orthosis according to Claim 17, wherein the securing means comprises a first strap means securable about one end of the rib and the patient's lower leg, and a second strap means securable about the other end of the rib and the patient's foot.

19. An orthosis according to Claim 17, wherein the securing means comprises a first strap means securable about one end of the rib and the patient's lower leg and a shoe for securing the other end of the rib to the patient's foot.

20. An orthosis according to Claim 17, wherein the securing means comprises an adhesive, at least end portions of the rib being adhered to the patient's lower leg and foot.

20

21. An orthosis according to any of Claims 17 to 20, wherein the rib is of plastics.

22. An orthosis according to any of Claims 17 to 20, wherein the rib is of silicone.

23. An orthosis according to any of Claims 17 to 21, wherein the rib is of polypropylene.

24. An orthosis according to any of Claims 17 to 20, wherein the rib is of ortholene.

30

25. An orthosis according to any of Claims 17 to 20, wherein the rib is of carbon

fibre.

26. An orthosis according to any preceding claim, wherein the orthosis is skin coloured.

5

27. An orthosis according to any preceding claim, wherein the orthosis is fabricated by injection moulding.

28. An orthosis according to any of Claims 17 to 20, wherein the orthosis is stamped or pressed from sheet material.

10

29. A kit comprising a plurality of orthoses according to any preceding claim, the orthoses being of varying size and shape for fitting to feet of different sizes and shapes.

15

30. A kit according to Claim 29, comprising differently coloured orthoses to allow the matching of the colour of the orthosis to the skin colour of the patient.

20

31. An orthosis substantially as hereinbefore described with reference to Figures 3 or 4, or to Figures 5, 6 and 7 of the accompanying figures.

32. A kit substantially as hereinbefore described.

1 / 3




FIG. 1a




FIG. 1b




FIG. 2a




FIG. 2b

2 / 3




FIG. 3




FIG. 4






FIG. 5

3 / 3



INTERNATIONAL SEARCH REPORT

Inter: onal application No.

PCT/GB 98/03068

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A61F 5/01

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 455934 A (A.PHILIPP), 24 December 1985 (24.12.85), column 4, line 41, figures 1,2, abstract --	1-16,29-32
X	US 5257969 A (C.MANCE), 2 November 1993 (02.11.93), column 3, line 19 - line 29; column 6, line 11 - line 14, figure 6 --	1-3
X	US 5676641 A (S.ARENSDORF ET AL), 14 October 1997 (14.10.97), figures 3,5, abstract --	1-3
X	US 3504668 A (R.E.BOUDON), 13 Sept 1967 (13.09.67), column 2, line 15 - line 19, figures 2-4 --	17-32

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 February 1999

Date of mailing of the international search report

25. 02. 1999

Name and mailing address of the ISA/



European Patent Office, P.B. 5818 Patentlaan 2
NL-2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

INGRID FALK

INTERNATIONAL SEARCH REPORT

International application No.

PCT/GB 98/03068

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4651723 A (K.SATOH), 24 March 1987 (24.03.87), figures 2-5 --	17
A	GB 2188550 A (JOHN ALAN DREW), 7 October 1987 (07.10.87), claim 9 -- -----	29-32

INTERNATIONAL SEARCH REPORT

International application No.

PCT/GB 98/ 03068

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

Claims 1-16 are related to an ankle-foot orthosis for resisting plantarflexion, comprising a resiliently flexible sock-like structure enveloping and claims 29-32 are related to a kit comprising the orthosis.

Claims 17-28 are related to an ankle-foot orthosis for resisting plantarflexion, comprising a resilient rib locatable along a portion of the dorsal aspect of the patient's foot and claims 29-32 are related to a kit comprising the orthosis.

The technical relationship between the two inventions defined in the claims lack a common special technical feature, which defines a contribution over the prior art.

SA 208851

INTERNATIONAL SEARCH REPORT

Information on patent family members

21/12/98

International application No.

PCT/GB 98/03068

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 455934 A	24/12/85	NONE	
US 5257969 A	02/11/93	NONE	
US 5676641 A	14/10/97	NONE	
US 3504668 A	13/09/67	NONE	
US 4651723 A	24/03/87	DE 3610532 A	01/10/87
GB 2188550 A	07/10/87	NONE	